



Extremely powerful; designated for use by World Expo 2010 Shanghai

Item	Model	F10ETL	F10ETS	F10ERL	F10ERS	F10ERL-T	F10ERS-T
Overall length	mm(in.)	1151(45.3)		703(27.7)			
Overall width	mm(in.)	430(16.9)		376(14.8)		376(14.8)	
Overall height	mm(in.)	1280(50.4)	1153(45.4)	1280(50.4)	1153(45.4)	1280(50.4)	1153(45.4)
Transom Height	mm(in.)	508(20.0)	381(15.0)	508(20.0)	381(15.0)	508(20.0)	381(15.0)
Weight	kg	66	64	68	66	72	70
Maximum power operation speed	r/min	4500					
Maximum continuous output	KW(hp)r/min	7.35(10)					
Rated voltage	V	48					
Maximum current	A	<180					
Motor efficiency	%	≥80					
Number pf stator		2					
Control system		Tiller control		Remote control			
Gear postions		Forward-Reverse					
Gear ratio		2.08(27/13)					
Trim and tilt system		Manual tilt				Electric tilt	
Gear oil capacity	cm3	320					
Propller options	in	3-9 7/8" x 11.25"					

\*Propeller choice will vary by boat size and application.

\*T=Back control, R=Front control, -T=Electric tilt