



Item	Model	F5ETL	F5ETS	F5ERL	F5ERS	F5ERL-T	F5ERS-T
Overall length	mm(in.)	717(28.2)		470(18.5)			
Overall width	mm(in.)	361(11.2)		286(11.3)		286(11.3)+120(4.7)	
Overall height	mm(in.)	1156(45.5)	1029(40.5)	1156(45.5)	1029(40.5)	1156(45.5)	1029(40.5)
Transom Height	mm(in.)	508(20.0)	381(15.0)	508(20.0)	381(15.0)	508(20.0)	381(15.0)
Weight	kg	30.4	29.4	29.4	28.4	29.5+4.8	28.5+4.8
Maximum power operation speed	r/min	4500					
Maximum continuous output	KW(hp)	3.7(5)r/min					
Rated voltage	V	48					
Maximum current	A	<100A					
Motor efficiency	%	≥80					
Number pf stator		1					
Control system		Tiller control		Remote control			
Gear postions		Forward-Reverse					
Gear ratio		2.08(27/13)					
Trim and tilt system		Manual tilt				Electric tilt	
Gear oil capacity	cm3	100					
Propller options	in	3-7.5" x 7" or 3-7.25" x 6"					

*Propeller choice will vary by boat size and application.

*T=Back control, R=Front control, -T=Electric tilt